





**Caratteristiche tecniche**


- Coefficiente di sicurezza fune 5:1.
- Conformi a DM2006/42/CE, EN13414-3.
- Anima metallica.

**Technical features**

- Wire rope safety factor 5:1.
- Compliant to DM2006/42/CE, EN13414-3.
- Wire core.

	
GRAM AD ANELLO Endless	GRLM CON LEGATURE With Eyes

GROMMET ANIMA METALLICA Wire Core Grommet							
Costruzione Construction	Code	Code	WLL 0° ≤ β < 7°	L1 (min)	AxB	Peso Weight	
							
			kg	m	mm	kg/m	
Ø 9 mm	7x7x19 r=1770	GRAM009	GRLM009	1.200	0,2	54x108	0,35
Ø 12 mm	7x7x19 r=1770	GRAM012	GRLM012	2.300	0,25	72x144	0,46
Ø 15 mm	7x7x19 r=1770	GRAM015	GRLM015	3.500	0,35	90x180	0,7
Ø 18 mm	7x7x19 r=1770	GRAM018	GRLM018	5.000	0,4	108x216	1,1
Ø 21 mm	7x7x19 r=1770	GRAM021	GRLM021	6.800	0,45	126x252	1,5
Ø 24 mm	7x7x19 r=1960	GRAM024	GRLM024	10.600	0,5	144x288	2
Ø 27 mm	7x7x19 r=1960	GRAM027	GRLM027	13.200	0,5	162x324	2,5
Ø 30 mm	7x7x19 r=1960	GRAM030	GRLM030	15.400	0,55	180x360	3,1
Ø 36 mm	7x7x19 r=1960	GRAM036	GRLM036	22.700	0,6	216x432	4,4
Ø 42 mm	7x7x19 r=1960	GRAM042	GRLM042	30.400	0,75	288x576	6
Ø 48 mm	7x7x19 r=1960	GRAM048	GRLM048	40.900	0,8	324x648	7,9
Ø 54 mm	7x7x19 r=1960	GRAM054	GRLM054	52.400	1	360x720	10
Ø 60 mm	7x7x19 r=1960	GRAM060	GRLM060	67.700	1,2	396x792	12,3
Ø 66 mm	7x7x19 r=1960	GRAM066	GRLM066	80.300	1,25	432x864	14,9
Ø 72 mm	7x7x19 r=1960	GRAM072	GRLM072	95.300	1,4	468x936	17,7
Ø 78 mm	7x7x19 r=1960	GRAM078	GRLM078	117.000	1,6	504x1008	20,8
Ø 84 mm	7x7x19 r=1960	GRAM084	GRLM084	142.000	1,7	576x1152	24
Ø 96 mm	7x7x19 r=1960	GRAM096	GRLM096	195.000	1,85	576x1152	31,4
Ø 108 mm	7x7x19 r=1960	GRAM108	GRLM108	262.000	2	648x1296	40



**COME ORDINARE - How to order:**

Aggiungere al codice principale, il relativo codice lunghezza.  
Add to the main code, the specific length code.

Ø 9mm, L= 1m

**GRAM009-010**

L	Lunghezza della braca Sling Length	1 m	1,5 m	2 m	2,5 m	3 m	4 m
	Codice lunghezza Length code	0100	0150	0200	0250	0300	0400